

- Versatile design and install options available
- Streamlined and flat façade aesthetic with concealed fixings
- Suitable for wall cladding and soffit only
- Pronounced "shadow line" effect between panels

# Product Specifications

Rib Height Available 25mm panel height (depth of recess)

Length of Panel

Panel lengths available from a minimum 500mm,

Pan Widths

205mm – 505mm panel widths (material dependant)

available Substrate

Substrate entions available forwall applications only

Requirements
Fire Rated/BAL

Applications

Suitable for use in fire rated and BAL applications in

conjunction with a suitable wall build up \*

\* Note: For further information and expert advice please contact Architectural Cladding Supplier.

### **Brands**

COLORBOND® steel
GALVABOND® steel

ZINCALUME® steel

**RHEINZINK®** 

Aurubis

KME

elZinc

Luxteel

VMZinc

#### Metals

Steel, Aluminium, Copper, Brass, Weathering Steel, Galvanised Steel, Titanium Zinc, Stainless Steel



# Key Benefits



### **Technical Support** & Installation

Architectural Cladding Suppliers are here to help you. We can manufacture and provide everything that is required to complete your project from our cladding profiles, to all the associated accessories and flashings via our sister company, PPC Flashings.

As every architectural project is different, if you require custom advice, we can discuss your project specifications and will work with you to fabricate to your individual requirements.

For any further technical support please contact Architectural Cladding Suppliers.







Web: www.acladding.com.au Email: admin@acladding.com.au Phone: 03 9775 1097 Address: 4 / 7 Silkwood Rise,

Carrum Downs, Victoria 3201

