

Product Specifications

Rib Heights 25mm and 38m

Available

Length of Panel Panel lengths available from a minimum 500mm,

dependant on material selection

Pan Widths
Available

165mm – 490mm pan widths from rib to rib (material

dependant)

Substrate Requirements Substrate options available for wall and roof

applications

Fire Rated/BAL Applications

Suitable for use in fire rated and BAL applications in conjunction with a suitable wall/roof build up *

* Note: For further information and expert advice please contact Architectural Claddina Suppliers

Brands

COLORBOND® steel GALVABOND® steel ZINCALUME® steel Luxteel

Metals

Steel, Weathering Steel, Galvanised Steel, Stainless Steel



Key Benefits

- Suited for residential and commercial building.
- Simple installation method with no specialist tools required.
- Custom pan widths available to suit design requirements.
- Minimal maintenance compared to other building materials.
- Sophisticated and clean
 aesthetic with no visible fixings
- Can be applied to a curved wall application.
- Ability to taper panels
- Versatile design and install options available.
- Allows for building expansion and contraction.



Technical Support & Installation

Architectural Cladding Suppliers are here to help you. We can manufacture and provide everything that is required to complete your project from our cladding profiles, to all the associated accessories and flashings via our sister company, PPC Flashings.

As every architectural project is different, if you require custom advice, we can discuss your project specifications and will work with you to fabricate to your individual requirements.

For any further technical support please contact Architectural Cladding Suppliers.







