

Product Specifications

Rib Heights available

25mm, 38mm and 50mm rib heights available

Length of Panel

Panel lengths available from a minimum 500mm,

dependant on material selectior

Pan Widths available

180mm – 530mm pan widths from rib to rib

(material dependant

Substrate Requirements Substrate options available for wall and roof

applications

Fire Rated/BAL Applications

Suitable for use in fire rated and BAL applications in conjunction with a suitable wall/roof build up *

* Note: For further information and expert advice please contact Architectural Cladding Supplier

Brands

COLORBOND® steel GALVABOND® steel ZINCALUME® steel

RHEINZINK®

Aurubis

KME

elZinc

Luxteel

VMZinc

Metals

Steel, Aluminium, Copper, Brass, Weathering Steel, Galvanised Steel, Titanium Zinc, Stainless Steel



Key Benefits

- Suited for residential and commercial building.
- Custom rib heights allow for various depth in shadow lines
- Custom pan widths available to suit design requirements.
- Ability to curve and taper panels.
- Double lock standing seam optional – recommended in areas where extreme weather conditions occur
- Minimal maintenance compared to other building materials.
- Versatile design and install options available.
- Allows for building expansion and contraction.



Technical Support & Installation

Architectural Cladding Suppliers are here to help you. We can manufacture and provide everything that is required to complete your project from our cladding profiles, to all the associated accessories and flashings via our sister company, PPC Flashings.

As every architectural project is different, if you require custom advice, we can discuss your project specifications and will work with you to fabricate to your individual requirements.

For any further technical support please contact Architectural Cladding Suppliers.





Not to scale



Web: www.acladding.com.au
Email: admin@acladding.com.au
Phone: 03 9775 1097
Address: 4 / 7 Silkwood Rise,

Carrum Downs, Victoria 3201

