

Shingle / Flatlock Order Form

Business Name: _____

Delivery Date: _____ AM PM

Contact Name: _____


Crane Lift: YES NO Time Required: _____

Phone Number: _____

Materials: _____

Delivery Address: _____

Stop ends and/or hooks for Flatlock products are highly recommended by Architectural Cladding Suppliers. If you are unsure, please contact us prior to ordering.



Client's Order No: Page: of

| Client ID/Area | COVER mm | Number of Panels Required | Panel Width mm | Panel Length mm | Bottom Hook Fold | ADDITIONAL COMMENTS |
|----------------|----------|---------------------------|----------------|-----------------|------------------|---------------------|
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

| *Clips | No Of Boxes |
|--|-------------|
| Shingle / Flatlock Clip Qty 200 | |
| *Note: Clips every 330mm (recommended) | |

IMPORTANT NOTICE TO CUSTOMERS

Please read carefully before submitting your order. Please ensure that measurements are accurate and correct. ACS will not be responsible for any errors as a result of an inaccurate or an incorrect order.

PRODUCT CHARACTERISTICS

Thermal expansion is a natural occurring characteristic of steel, copper, titanium, zinc and aluminium products. Therefore, ACS cannot adjust manufacturing processes to reduce thermal expansion.

MATERIAL HANDLING AND DELIVERIES

All products should be kept dry prior to installation. If product becomes wet, separate and dry immediately and always handle with care.

ESTIMATED DELIVERY TIMES

Delivery times are subject to change and times and dates are estimates only.

CLAIMS

ACS will not recognise claims after 7 days.

MEASUREMENTS

All measurements must be in millimetres and tolerances as follows:-

- SHEET LENGTH +/- 7MM AND
- COVERING WIDTH +/- 7MM

GENERAL TERMS AND CONDITIONS OF SALE AND SUPPLY

Please note that all product supplied by ACS are subject to ACS' Terms & Conditions of Sale and Supply which are incorporated by reference into every contract for the supply of Goods or Services. For our current Terms go to www.acladding.com.au/termsandconditions

INSTALLATION

ACS recommends that our cladding products are installed by a qualified and experienced cladding installers for best results. Our ACS datasheet is to be used as a guide only and for further technical support or advice, please contact our cladding team, prior to placing your order or any installation works.

Signature:

Date:

Notes or Special Fold Requests

Architectural Cladding Suppliers

PO Box 688
Patterson Lakes Vic 320

www.acladding.com.au

Phone: 03 9775 1097

Email: admin@acladding.com.au

Fax or Email Order Forms to:

Fax: (03) 9708 2275

Email: admin@acladding.com.au

