## Standing Seam Order Form

Phone Number:  Delivery Address:  Stop ends and/or hooks to each panel are highly recommended by contact us prior to ordering.								Delivery Date: AM PM  Crane Lift: YES NO Time Required:  Materials:  by Architectural Cladding Suppliers. If you are unsure, please  To be trimmed			
Please Select:  25mm 38mm 50mm				BOTTOM trimmed on site 20mm Standard			mmed n site	END - TO	on site	Right to Left Panel Direction	
Client's Order No: Page: of											
Client ID/Area	COVER mm	Number of Panels Required	Panel Length mm	Bottom Hook Fold	Top 9 Stop End	o° Fold Fold Back	Panel D Left to Right			MMENTS	
*Clips	No Of Boxes 'Clips				No Of B	oxes	IMPORTANT NOTICE TO CUSTOMERS Please read carefully before submitting your order. Please ensure that measurements are accurate and correct. ACS will not be responsible for any errors as a result of an inaccurate or an incorrect order.  PRODUCT CHARACTERISTICS				
25mm Fixed Qty 500			iding 00								
38mm Fixed Qty 500	38mm Slic Qty 400						Thermal expansion is a natural occurring characteristic of steel, copper, titanium, zinc and aluminium products. Therefore, ACS cannot adjust manufacturing processes to reduce thermal expansion.  MATERIAL HANDLING AND DELIVERIES All products should be kept dry prior to installation. If product becomes wet, separate and dry immediately and always handle with care.  ESTIMATED DELIVERY TIMES				
50mm Fixed Qty 400	50mm Sliding Qty 400										
*Note: Clips every 330mm (recommended)							Delivery times are subject to change and times and dates are estimates only.  CLAIMS  ACS will not recognise claims after 7 days.				
Notes or Special Fold Requests							MEASUREMENTS  All measurements must be in millimetres and tolerances as follows:-  SHEET LENGTH +/- 7MM AND  COVERING WIDTH +/- 7MM  GENERAL TERMS AND CONDITIONS OF SALE AND SUPPLY Please note that all product supplied by ACS are subject to ACS' Terms & Conditions of Sale and Supply which are incorporated by reference into every contract for the supply of Goods or Services. For our current Terms go to www. acladding.com.au/termsandconditions  INSTALLATION  ACS recommends that our cladding products are installed by a qualified and experienced cladding installers for best results. Our ACS datasheet is to be used as a guide only and for further technical support or advice, please contact our cladding team, prior to placing your order or any installation works.				
								Signature:  Date:			
								Date.			

## **Architectural Cladding Suppliers**

PO Box 688 Patterson Lakes Vic 320 www.acladding.com.au Phone: 03 9775 1097

Email: admin@acladding.com.au

Fax or Email Order Forms to: Fax: (03) 9708 2275

Email: admin@acladding.com.au

